

Technische Fiche: DTS428080-

S-Rack Serverkast 19" 42HE HxBxD 1954x800x800mm zwart

Afwerking RAL9005 zwart, IP20, max. draagvermogen 1000kg



SCHRACK-Info

Server cabinets are mainly used in data centers and server rooms where an increased load is required and heavy installations such as servers, UPS, etc., have to be installed.

The maximum load is 1000kg.

Front door: Perforated (70%) metal door arched.

Rear door: Perforated (70%), split metal door arched.

The side panels of the server cabinet can be removed and allows easy access to all installations from all sides.

The server cabinet is cooled both actively and passively.

The cooling works passively via perforated doors and actively via roof fans.

The 19" server cabinet from Schrack Technique ensures a high level of flexibility in cable entry due to the prepared opening option in the upper area.

TECHNICAL DATA


- Colour: RAL9005 black
- The opening angle of the front door is up to 230°C
- Height: 42U
- Width: 800mm
- Depth: 800mm
- Degree of protection: IP20
- Maximum load: 1000kg

- Doors: Rear doors are in standard 70% perforated, double door with 3 point locking system. Front door monoblock 70% perforated, arched metal door with 4 point locking system and swing handle lock, RAL9005 black.
- The side panels are lockable and removable with a cylinder lock
- Fan: Installation is from the roof, no interference with installed equipment or cables inside the cabinet.
- Cable entry option: In the top cover with sliding rubber edge.
- Structure of the enclosure: 19" rails are bent 4-times for reasons of strength. 2.0mm thickness ensure high resilience. The 19" rails are made of steel with an 8 – 12 micron zinc coating for corrosions resistance.




Technische gegevens

Breedte (mm)	800,00
Hoogte (mm)	1.954,00
Diepte (mm)	800,00
Nettogewicht (kg)	113,69
EAN CODE	9004840895339
Omgevingstemperatuur min. (°C)	5
Omgevingstemperatuur max. (°C)	40
Hoogte eenheden	42
Afwerking	RAL 9005
Beschermingsgraad	IP20


Afmetingen (mm)

BOTTOM VIEW


Afmetingen (mm)




FRONT VIEW



SIDE VIEW




REAR VIEW

Afmetingen (mm)

TOP VIEW

Detailtekening



Omschrijving	Referentie
S-Rack Serverkast 19" 42HE HxBxD 1954x800x800mm zwart	DTS428080
Afwerking RAL9005 zwart, IP20, max. draagvermogen 1000kg	