

Technische Fiche: G163212106

Klokboor snijdiepte 36mm Ø121mm zonder snelspanner



Schrack-Info

Designation: HSS bimetal cylinder hole saw, without shank.

Materials to be cut: steel, stainless steel, cast iron, copper, bronze, aluminium, wood and plastic to a certain extent.

Features: :

- Very fast sawing progress
- Minimised rattling and squeaking
- Cutting depth: 36mm
- Vario toothing
- M42 bimetal (8% cobalt)

Technische gegevens

Hoogte (mm)	43,00
Netto diameter (mm)	121,00
Nettogewicht (kg)	0,64
Product	Klokboor
Leverancier	Würth

Gegevens tabel: Klokboor snijdiepte 36mm Ø121mm zonder snelspanner

Modelle		GI63212106	GI63268061	GI63290105	GI63290114
Abmessungen	mm	21	68	105	114
	Zoll	13/16	2 11/16	4 1/8	4 1/2
Empholene Drehzahlen 1 / min	Weicher Stahl	425	130	80	75
	WS VA	210	65	40	35
	Gußeisen	280	85	55	50
	Messing	560	165	110	100
	Alu	630	190	120	105
Verpackungseinheiten		1			

Omschrijving	Referentie
Klokboor snijdiepte 36mm Ø121 mm zonder snelspanner	GI63212106