



Technische Fiche: HLP29CC01F

FO Patchkabel Duplex SC/SC 9/ 125µm OS2 LSOH-3 geel 1m

LSOH, yellow



SCHRACK-Info

Single mode patch cords are used for telecom networks and also used for high speed metropolitan and access network. The single-mode patch cables are equipped with an LSOH jacket. These comply with IEC or EIA-TIA standards. These singlemode enhanced patch cords are terminated with optimized connectors which give optimum optical performance.

FEATURES

- SC/UPC - SC/UPC connectors
- Low smoke zero halogen (LSOH) jacket
- 900 µm tight buffer
- Singlemode cabled fiber conforms to ITU-T G.657.A2, IEC 60793-2-50
- Duplex
- REACH, RoHS and SvHC materials compliant

APPLICATIONS

- CATV / Video
- Passive Optical Network PON
- WDM / DWDM
- FTTH
- Data centers
- Supports high speed multi channel video, data and voice services in metropolitan and access networks


- ATM, SONET and WDM



Technische gegevens

Productnormen	IEC 61300-3-4 / IEC 61300-3-6
Connector standaard	IEC 61754
FO aansluitingen	SC/SC
Lengte patchsnoer (m)	1,0
Type vezels	9/125µm OS2 singlemode
Kabelmantel	LS0H
Afwerking	Geel
Insertion loss typical (dB)	≤0,25
Return loss typical (dB)	≥50
Omgevingstemperatuur min. (°C)	-20
Omgevingstemperatuur max. (°C)	60
Nettogewicht (kg)	0,05

Maattekening: FO Patchkabel Duplex SC/SC 9/125µm OS2 LS0H-3 geel 1m



Omschrijving	Referentie
FO Patchkabel Duplex SC/SC 9/125µm OS2 LSOH-3 geel 1m LSOH, yellow	HLP29CC01F