


Technische Fiche: HSELS123LR

FO Splicebox DIN-rail 12x pigtails LC

50/125µm OM3



RAL7035, incl. Pigtails, incl. couplers, CLASSIC



Technische gegevens

Breedte (mm)	126,00
Hoogte (mm)	35,20
Diepte (mm)	155,65
Nettogewicht (kg)	0,59
Type vezels	50/125µm OM3 multimode
Afwerking	RAL 7035
Insertion loss typical (dB)	≤0,2
Return loss typical (dB)	≥35
Omgevingstemperatuur min. (°C)	-10
Omgevingstemperatuur max. (°C)	70
Aantal glasvezels	12
Glasvezelaansluiting	LC

Maattekening: FO Splicebox DIN-rail 12x pigtails LC 50/125µm OM3



Artikelen

Omschrijving	Referentie
FO Splicebox DIN-rail 12x pigtails LC 50/125µm OM3 RAL7035, incl. Pigtails, incl. couplers, CLASSIC	HSELS123LR
Optionele toebehoren	
FO Splice lasbescherming 60mm (verpakking 10stk.)	HELSP00011
FO Splice lasbescherming 45mm (verpakking 10stk.)	HELSP00010
Glasvezelreinigingsstift LC en MU Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	HSELSZT001
OPM200 Glasvezeltester voor vermogensmeting	HSELSZT003
FO Patchkabel Duplex LC/LC 50/125µm OM3 LS0H-3 aqua 2m LS0H, aqua	HLP23LL02F
FO Patchkabel Duplex LC/LC 50/125µm OM3 LS0H-3 aqua 5m LS0H, aqua	HLP23LL05F

Artikelen

Omschrijving	Referentie
Optionele toebehoren	
FO Patchkabel Duplex LC/SC 50/125µm OM3 LSOH-3 aqua 2m Aqua	HLP23LC02F
FO Patchkabel Duplex LC/SC 50/125µm OM3 LSOH-3 aqua 5m LSOH, aqua	HLP23LC05F
FO Patchkabel Duplex LC/ST 50/125µm OM3 LSOH-3 aqua 2m LSOH, aqua	HLP23LT02F
FO Patchkabel Duplex LC/ST 50/125µm OM3 LSOH-3 aqua 5m LSOH, aqua	HLP23LT05F