


Technische Fiche: HSELSK03MR

Glasvezelkoppeling LC/UPC-simplex kunststof OM3

without flange, aqua, dustcover-shutter, CLASSIC



Technische gegevens

Breedte (mm)	19,00
Hoogte (mm)	10,00
Nettogewicht (kg)	0,01
Type vezels	50/125µm OM3 multimode
Afwerking	Groen
Insertion loss typical (dB)	≤0,2
Omgevingstemperatuur min. (°C)	-40
Omgevingstemperatuur max. (°C)	80
Productgamma	Koppeling

Artikelen

Omschrijving	Referentie
Glasvezelkoppeling LC/UPC-simplex kunststof OM3 without flange, aqua, dustcover-shutter, CLASSIC	HSELSK03MR
Optionele toebehoren	
FTTH Opbouwbehuizing 80x80x28mm leeg voor 4-fibers wit RAL9010 Pure white, also suitable for DIN-rail installation	HSELDA40WP
FTTH Pigtail LC 50/125µm OM3 1m 4pcs. Easy Strip, colored according to IEC 60304, CLASSIC	HLP03M041P
FO Pigtail LC 50/125µm OM3 2m 4stks. colored according to IEC 60304, CLASSIC	HLP03L042P
FO Pigtail LC 50/125µm OM3 2m 8stks. colored according to IEC 60304, CLASSIC	HLP03L082P
FO Pigtail LC 50/125µm OM3 2m 12stks. colored according to IEC 60304, CLASSIC	HLP03L122P