

Technische Fiche: HSELSK09GR






FFTH Glasvezelkoppeling SC/APC-Simplex plastiek OS2

without flange, green, dustcover-shutter, CLASSIC



Technische gegevens

Breedte (mm)	19,00
Hoogte (mm)	10,00
Nettogewicht (kg)	0,01
FO aansluitingen	SC/APC
Type vezels	9/125µm OS2 Singlemode/ G.657.A2
Afwerking	Groen
Insertion loss typical (dB)	≤0,2
Omgevingstemperatuur min. (°C)	-40
Omgevingstemperatuur max. (°C)	75
Productgamma	Koppeling

Afmetingen (mm)

[mm]

Artikelen

Omschrijving	Referentie
FFTH Glasvezelkoppeling SC/APC-Simplex plastic OS2 without flange, green, dustcover-shutter, CLASSIC	HSELSK09GR
Optionele toebehoren	
FFTH Opbouwbehuizing 80x80x28mm leeg voor 4-fibers wit RAL9010 Pure white, also suitable for DIN-rail installation	HSELDA40WP
FFTH Pigtaills SC/APC 8° OS2 9/125µm G657.A2 l=1m 4 stuks Easy Strip, colored according to IEC 60304, CLASSIC	HLP09D041P
FO Pigtail SC/APC 9/125µm OS2 2m 4stks. colored according to IEC 60304, CLASSIC	HLP09D042P
FO Pigtail SC/APC 9/125µm OS2 2m 8stks. colored according to IEC 60304, CLASSIC	HLP09D082P
FO Pigtail SC/APC 9/125µm OS2 2m 12stks. colored according to IEC 60304, CLASSIC	HLP09D122P