

Technische Fiche: IG009405--

Cable management enclosure Series J, dotted, 2 doors, size 2

H=1100 W=1130 D=320mm, door opening angle 180°



Technische gegevens

Breedte (mm)	1.130,00
Hoogte (mm)	1.100,00
Diepte (mm)	320,00
EAN CODE	4029155605294
Stroomwarmteverliezen (W)	-413,71
Uitvoering	Polyester glasvezelversterkt kunststof
Product	Kabelverdeelkast KVS
Hoogte (mm)	1100
Breedte (mm)	1115
Diepte (mm)	320
Aantal deuren	2
Aantal deuren	Dubbele deur geribbeld
Sluitingen	Zwenkgreep met halve cilinder
Afwerking	RAL 7035
Beschermingsgraad	IP44
Beschermingsklasse	II
Slagvastheid	IK10

Artikelen

Omschrijving	Referentie
Cable management enclosure Series J, dotted, 2 doors, size 2 H=1100 W=1130 D=320mm, door opening angle 180°	IG009405
Optionele toebehoren	
Mountingplate for IG009405, H=985 W=1035 D=6mm including fastening screws, mounting plate made of melamine-laminated hard paper	IG009445
plastic base frame sizes 2/S6 1200/400 plastic base frame serving as a foundation for plinth	IG790330
base filler - hydrophobic 100 liter bag, water-repellent - hydrophobic	IG790333
base filler expanded clay 4-8mm round 50L water-absorbing - expanded clay, 50 liter bag	IG790570
foam insert size 2/S6/310 (absorption mat)	IG793820
Plinth Polyester Series J size 2X , RAL7035 H=905 W=1110 D=310mm	IG009315
Adapter bar for KVS - IG009405, size 2 (PU=2 pcs.) Pre-cut with M6 machine tap bit	IG009465
	CSIL129421
Modular chassis 4-21K, 7-rows, complete Front plates sheet steel	IL148421-A
self-cutting Lens Head Screw M6 (PU = 4Pieces) for fastening the adapter bars IG900461--, IG009462--, IG009463-- and IG009465--	IG009000