


Technische Fiche: IL198578-A

# Metering insert 5-28G compl. 10 cou. pl. front pl. st. STMK

Frontblende Stahlblech



## Technische gegevens

|                       |                       |
|-----------------------|-----------------------|
| Breedte (mm)          | 1.140,00              |
| Hoogte (mm)           | 1.290,00              |
| Diepte (mm)           | 102,00                |
| EAN CODE              | 9004840967739         |
| Product               | Tellerverdeelinzet    |
| Provincie             | Steiermark            |
| Chassisdelen          | Frontplaten kunststof |
| Afwerking             | RAL 7035              |
| Breedte kast          | 5                     |
| Hoogte eenheden       | 28                    |
| Aantal rijen          | 2                     |
| Tellerplaatsen        | 10                    |
| Secundaire rijen      | 1                     |
| Materiaal frontplaten | Plaatstaal            |
| Omschrijving          | Inzet                 |

## Artikelen

| Omschrijving                                                                                                                                                                                                                                                                                                                                                   | Kopergewicht (kg/km) | Referentie |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|------------|
| Metering insert 5-28G compl. 10 cou. pl. front pl. st. STMK<br>Frontblende Stahlblech                                                                                                                                                                                                                                                                          |                      | IL198578-A |
| <b>Optionele toebehoren</b>                                                                                                                                                                                                                                                                                                                                    |                      |            |
| Aardingsverbinding 300mm 6mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                      |                      | IL900099   |
| Plug-in counter bar 50A for Vienna, Tyrol and Styria<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019         |                      | IL900189   |
| Plug-in counter bar 50A, PU = 64 Pieces<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019                      |                      | IL900189-A |
| Plug-in counter bar pins 63A, 44mm, PU=7 pieces                                                                                                                                                                                                                                                                                                                |                      | IL900190   |
| Cover for Plug-in counter bars                                                                                                                                                                                                                                                                                                                                 |                      | IL900191   |
| Meter Connection Terminal 50A for Czech Republic, wired 1,3m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 975                  | IL901816   |
| Meter Connection Terminal 50A for Czech Republic, wired 1,8m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 1350                 | IL901820   |
| Meter Connection Terminal 50A for Czech Republic, wired 2,3m<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | 1725                 | IL901824   |