


Technische Fiche: IP3270091 -

## Disconnect terminal block PTC 2, 5-TWIN-TG

Push-in connection, 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, 20 A, 400 V, length: 67.8 mm, width: 5.2 mm, grey



### Technische gegevens

|                                                                                     |                   |
|-------------------------------------------------------------------------------------|-------------------|
| Diepte (mm)                                                                         | 36,50             |
| Breedte (mm)                                                                        | 5,20              |
| Hoogte (mm)                                                                         | 67,80             |
| Nettogewicht (kg)                                                                   | 0,01              |
| EAN CODE                                                                            | 4046356959940     |
| Stroomwarmteverliezen (W)                                                           | 0,77              |
| Omgevingstemperatuur min. (°C)                                                      | -40               |
| Omgevingstemperatuur max. (°C)                                                      | 120               |
| Omschrijving                                                                        | Klemmen           |
| Systeem                                                                             | Push-In           |
| Productgamma                                                                        | PT                |
| Productgroep                                                                        | Scheidingsklemmen |
| Maximale aansluitcapaciteit vaste geleiders (mm <sup>2</sup> )                      | 4                 |
| Maximale aansluitcapaciteit soepele geleiders (mm <sup>2</sup> )                    | 2,50              |
| Maximale aansluitcapaciteit soepele geleiders met adereindhulzen (mm <sup>2</sup> ) | 2,50              |
| Minimale aansluitcapaciteit vaste geleiders (mm <sup>2</sup> )                      | 0,14              |
| Minimale aansluitcapaciteit soepele geleiders (mm <sup>2</sup> )                    | 0,14              |

## Technische gegevens - vervolg

|                                                                                     |       |
|-------------------------------------------------------------------------------------|-------|
| Minimale aansluitcapaciteit soepele geleiders met adereindhulzen (mm <sup>2</sup> ) | 0,14  |
| Aansluitcapaciteit (mm <sup>2</sup> )                                               | 2,5   |
| Afwerking                                                                           | Grijs |
| Nominale stroom (A)                                                                 | 20    |

## Artikelen

| Omschrijving                                                                                                                                                                | Referentie |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| Disconnect terminal block PTC 2,5-TWIN-TG<br>Push-in connection, 0.14 mm <sup>2</sup> - 4 mm <sup>2</sup> , AWG: 26 - 12, 20 A, 400 V, length: 67.8 mm, width: 5.2 mm, grey | IP3270091  |
| <b>Optionele toebehoren</b>                                                                                                                                                 |            |
| End bracket CLIPFIX 15, to be snapped onto NS 15 DIN rail<br>Snap-on end bracket, color: gray                                                                               | IP3022263  |
| End bracket CLIPFIX 35-5, for NS 35/7,5 or NS 35/15<br>Quick mounting end clamp, with marking option, width: 5.15 mm, color: gray                                           | IP3022276  |
| End bracket CLIPFIX 35, for NS 35/7,5 DIN rail or NS 35/15<br>Quick mounting end clamp, with marking option, width: 9.5 mm, color: gray                                     | IP3022218  |
| End bracket E/UK<br>End clamp, Width: 9.5 mm, Height: 35.3 mm, Length: 50.5 mm, Color: gray                                                                                 | IP1201442  |
| End bracket E/UK 1<br>End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray                                        | IP1201413  |
| End bracket E/MBK<br>End clamp, width: 6.2 mm, color: gray                                                                                                                  | IP1401637  |
| End bracket E/MK 1<br>End clamp width: 6 mm, color: gray                                                                                                                    | IP1421659  |
| End bracket E/NS 35 N<br>End clamp, width: 9.5 mm, color: gray                                                                                                              | IP0800886  |
| Zack marker strip ZB 5, consecutive numbers 1-10<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm                | IP10500171 |
| Zack marker strip ZB 5, consecutive numbers 11-20<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm               | IP10500172 |
| Zack marker strip ZB 5, consecutive numbers 21-30<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm               | IP10500173 |

## Artikelen

| Omschrijving                                                                                                                                                   | Referentie |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>Optionele toebehoren</b>                                                                                                                                    |            |
| Zack marker strip ZB 5, consecutive numbers 31-40<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm  | IP10500174 |
| Zack marker strip ZB 5, consecutive numbers 41-50<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm  | IP10500175 |
| Zack marker strip ZB 5, consecutive numbers 51-60<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm  | IP10500176 |
| Zack marker strip ZB 5, consecutive numbers 61-70<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm  | IP10500177 |
| Zack marker strip ZB 5, consecutive numbers 71-80<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm  | IP10500178 |
| Zack marker strip ZB 5, consecutive numbers 81-90<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm  | IP10500179 |
| Zack marker strip ZB 5, consecutive numbers 91-100<br>Strip, white, snap into tall marker groove, for terminal width: 5.15 mm, lettering field: 5.15 x 10.5 mm | IP1050017H |
| Zack marker strip flat ZBF 5, consecutive numbers 1-10<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm    | IP08086711 |
| Zack marker strip flat ZBF 5, consecutive numbers 11-20<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086712 |
| Zack marker strip flat ZBF 5, consecutive numbers 21-30<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086713 |
| Zack marker strip flat ZBF 5, consecutive numbers 31-40<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086714 |
| Zack marker strip flat ZBF 5, consecutive numbers 41-50<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086715 |
| Zack marker strip flat ZBF 5, consecutive numbers 51-60<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086716 |
| Zack marker strip flat ZBF 5, consecutive numbers 61-70<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086717 |
| Zack marker strip flat ZBF 5, consecutive numbers 71-80<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086718 |
| Zack marker strip flat ZBF 5, consecutive numbers 81-90<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm   | IP08086719 |
| Zack marker strip flat ZBF 5, consecutive numbers 91-100<br>Strip, white, snap into flat marker groove, for terminal width: 5 mm, lettering field: 5 x 5.2 mm  | IP0808671H |
| End cover D-PTC 2,5-TWIN-MT<br>End cover, length: 67.8 mm, width: 2.2 mm                                                                                       | IP3270100  |
| Plug-in bridge FBS 2-5<br>Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 9 mm, poles: 2, color: red                                                    | IP3030161  |

## Artikelen

| Omschrijving                                                                                                                                          | Referentie |
|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>Optionele toebehoren</b>                                                                                                                           |            |
| Plug-in bridge FBS 3-5                                                                                                                                | IP3030174  |
| Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 14.2 mm, poles: 3, color: red                                                                  |            |
| Plug-in bridge FBS 4-5                                                                                                                                | IP3030187  |
| Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 19,4 mm, poles: 4, color: red                                                                  |            |
| Plug-in bridge FBS 5-5                                                                                                                                | IP3030190  |
| Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 24.6 mm, poles: 5, color: red                                                                  |            |
| Plug-in bridge FBS 10-5                                                                                                                               | IP3030213  |
| Plug-in bridge, pitch: 5.2 mm, length: 22.7 mm, width: 50.6 mm, poles: 10, color: red                                                                 |            |
| Plug-in bridge FBS 20-5                                                                                                                               | IP3030226  |
| Plug-in bridge, pitch: 5.2 mm, poles: 20, color: red                                                                                                  |            |
| Plug-in bridge FBSR 2-5                                                                                                                               | IP3033702  |
| Plug-in bridge, pitch: 5.2 mm, poles: 2, color: red                                                                                                   |            |
| Plug-in bridge FBSR 3-5                                                                                                                               | IP3001591  |
| Plug-in bridge, pitch: 5.2 mm, poles: 3, color: red                                                                                                   |            |
| Plug-in bridge FBSR 5-5                                                                                                                               | IP3001593  |
| Plug-in bridge, pitch: 5.2 mm, poles: 5, color: red                                                                                                   |            |
| Test adapter PAI-4-N GY                                                                                                                               | IP3032871  |
| Test adapter, color: grey                                                                                                                             |            |
| Screwdriver 0.6 x 3.5 ( SZF 1-0.6X3.5)                                                                                                                | IP1204517  |
| Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip |            |