

Technische Fiche: IUKTS6301A

Cooling unit 1500W, outer mounting on the side, Series DTS

400V, IP55, RAL 7035



SCHRACK-Info

General:

- Cooling unit for outer mounting on the door or side (=DTS)
- Compact design for smaller enclosures or to cool hot spots
- Technical design with a standard controller
- Color: RAL 7035 (Light grey)

IUKTS6301:

- Cooling performance: 1500W
- Rated voltage: 400V
- Very high energy efficiency ratio (EER)
- Service friendly due to direct access to the PCB and the fans, thus 80 % shorter repair times
- Type of connection: Spring-type terminal included with plug
- Degree of protection IP55: Towards the enclosure
- Degree of protection IP34: Towards the surroundings


Technische gegevens

Breedte (mm)	399,00
--------------	--------


Technische gegevens - vervolg

Hoogte (mm)	966,00
Diepte (mm)	244,00
Nettogewicht (kg)	45,00
Omgevingstemperatuur min. (°C)	15
Omgevingstemperatuur max. (°C)	55
Beschermingsgraad	IP55
Beschermingsklasse	I
Nominale spanning	400VAC
Product	Koeltoestel
Koelvermogen (W)	1500

Kennlijnen Kühlleistung



Dimensions and Cutout IUKTI6201A



Omschrijving	Referentie
Cooling unit 1500W, outer mounting on the side, Series DTS 400V, IP55, RAL 7035	IUKTS6301A