

Technische Fiche: LI158834--

# I-VIDUAL LED Paneel 620x620mm UGR<19

## 4000K wit



### Technische gegevens

|                          |            |
|--------------------------|------------|
| Netto lengte (mm)        | 617,00     |
| Breedte (mm)             | 617,00     |
| Hoogte (mm)              | 13,00      |
| Nettogewicht (kg)        | 4,66       |
| Leverancier              | SLV        |
| Verblindingsfactor (UGR) | <22        |
| Lampfitting              | LED        |
| LxBxH mm                 | 617x617x13 |

## Artikelen

| Omschrijving                                                                | Referentie |
|-----------------------------------------------------------------------------|------------|
| I-VIDUAL LED Paneel 620x620mm UGR<19 4000K wit                              | LI158834   |
| <b>Optionele toebehoren</b>                                                 |            |
| Universele opbouw kader LED-paneel 620x620mm wit                            | LI158772   |
| INSTALLATION FRAME, silver-grey, L/W 62.5/62.5 cm<br>for I-VIDUAL LED panel | LI158774   |
| Plafondrozet 10,3x22x5,1 cm mat wit                                         | LI158791   |
| Pendelset voor LED paneel                                                   | LI158799   |
| TCI LED-Driver 50VA 350-1050mA DIP-Switch DALI<br>inkl. Cable relief        | LI464032   |
| LED-Driver 40W 1000mA incl. trekontlasting                                  | LI464170   |
| LED-Driver 40W 1000mA incl. trekontlasting dimbaar                          | LI464176   |