

Technische Fiche: LID13987--

Sutil rond 2 LED 30W 4000K 2100lm 120°

IP40 wit **ECONOMY**

Downlighter LED, boordiameter Ø285mm - driver inclusief



Productinformatie

30W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 700mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.




Technische gegevens

Lichtstroom (lm)	2100
Lichtkleur	Koudwit
Kleurtemperatuur (K)	4000
Kleurweergave-index (Ra)	≥80
Levensduur	30.000h
Regelen lichtintensiteit	Neen
Beschermingsklasse	II
Beschermingsgraad	IP40
Type verlichting	LED-Paneel
Lichtmiddel inbegrepen	Inbegrepen

Technische gegevens - vervolg

Aantal lampen	1
Lampvoet	LED
Stralingshoek (°)	120
Lichtrendement (lm/W)	70
Cos Phi	0,9
Vermogen (W)	30
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Frequentie (Hz)	50/60
Bevestiging	Plafondinbouw
Boring voor inbouw (mm)	Ø 285
Inbouw diepte (mm)	50
Afwerking	Wit
Uitvoering	Acryl Kunststof Aluminium gegoten
Hoogte (mm)	22
Diameter (mm)	295
Optionele toebehoren	LID 16598--
ØxH (mm)	295x22
Uitsnijding (mm)	Ø 285

Maattekening: Sutil rond 2 LED 30W 4000K 2100lm 120° IP40 wit



Artikelen

Omschrijving	Referentie
Sutil rond 2 LED 30W 4000K 2100lm 120° IP40 wit	LID13987
Downlighter LED, boordiameter Ø285mm - driver inclusief	
Optionele toebehoren	
LED Driver 180mA-1500mA 230VAC DALI/ Push DIM/ TRIAC/ 1-10V	LID16598
IP20 230V; 23 DRIVERS	