

Technische Fiche: LID15774--

# Linear BU LED 40/20W 4000K 34°/120° 220-240V IP20 wit

Aluminium profiel verlichting 3800lm direct / 1800lm indirect



## Productinformatie

40W UGR17 Linear system with with 48 LED spots and 20W uplight for suspended installation, ideal for offices. \_x000D\_ \_x000D\_ Complete with 1000mA + 500mA drivers\_x000D\_ \_x000D\_ Complies with standard EN60598-1 and any other specific standards.

## Technische gegevens

|                          |              |
|--------------------------|--------------|
| Lichtstroom (lm)         | 1800<br>3800 |
| Lichtkleur               | Koudwit      |
| Kleurtemperatuur (K)     | 4000         |
| Kleurweergave-index (Ra) | ≥90          |
| Verblindingsfactor (UGR) | <17          |
| Regelen lichtintensiteit | Neen         |
| Beschermingsklasse       | I            |
| Beschermingsgraad        | IP20         |
| Lichtmiddel inbegrepen   | Inbegrepen   |
| Lampvoet                 | LED          |
| Stralingshoek (°)        | 34/120       |

## Technische gegevens - vervolg

|                              |               |
|------------------------------|---------------|
| Vermogen (W)                 | 90/95         |
| Lichtrendement (lm/W)        | 95 / 90       |
| Cos Phi                      | 0,9           |
| Vermogen (W)                 | 40<br>20      |
| Voedingen                    | LED Driver    |
| Nominale werkspanning AC (V) | 220-240       |
| Bedrijfsstroom mA (mA)       | 500/1000      |
| Frequentie (Hz)              | 50/60         |
| Bevestiging                  | Pendelmontage |
| Pendellengte (mm)            | 300           |
| Afwerking                    | Wit           |
| Uitvoering                   | Aluminium     |
| Lengte (mm)                  | 1300          |
| Breedte (mm)                 | 70            |
| Hoogte (mm)                  | 35            |
| Optionele toebehoren         | LID15782--    |
| LxBxH (mm)                   | 1300x70x35    |

## Artikelen

| Omschrijving                                                  | Referentie |
|---------------------------------------------------------------|------------|
| Linear BU LED 40/20W 4000K 34°/120° 220-240V IP20 wit         | LID 15774  |
| Aluminium profiel verlichting 3800lm direct / 1800lm indirect |            |
| <b>Optionele toebehoren</b>                                   |            |
| Hoekprofiel 90° voor linear profiel A, B, BU wit              | LID 15782  |
| Montage toebehoren                                            |            |