

Technische Fiche: LID17282--

50140BU/W/V WHITE 40W CCTV 60x60 UGR19 PANEL IP20 BACKLIT

complete with 1000mA driver; 06 DOWNLIGHT FIX LED



Productinformatie

60x60 adjustable CCT recessed backlit LED panel with microprismatic diffuser for T-rail false ceilings. Uniform lighting, ideal for commercial applications. Complete with 1000mA driver. Complies with standard EN60598-1 and any other specific standards.

Technische gegevens

Lichtstroom (lm)	3600/4000/3800
Lichtkleur	Koudwit Warmwit Neutraalwit
Kleurtemperatuur (K)	4000 3000 5700
Kleurweergave-index (Ra)	≥80
Verblindingsfactor (UGR)	<19
Regelen lichtintensiteit	Neen
Beschermingsklasse	II
Beschermingsgraad	IP20
Type verlichting	LED-Paneel

Technische gegevens - vervolg

Lichtmiddel inbegrepen	Inbegrepen
Lampvoet	LED
Lichtrendement (lm/W)	90
Cos Phi	0,90
Vermogen (W)	40
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Ingangsspanning AC (V)	220-240
Bedrijfsstroom mA (mA)	1000
Primaire stroom (A)	1
Frequentie (Hz)	50/60
Bevestiging	Plafondinbouw
Inbouw diepte (mm)	60
Afwerking	Wit
Uitvoering	Aluminium Staal
Lengte (mm)	595
Breedte (mm)	595
Hoogte (mm)	30
Optionele toebehoren	LID16949--
LxBxH (mm)	595x595x30

Artikelen

Omschrijving	Referentie
50140BU/W/V WHITE 40W CCTV 60x60 UGR19 PANEL IP20 BACKLIT complete with 1000mA driver; 06 DOWNLIGHT FIX LED	LID17282
Optionele toebehoren	
Schroefloze klem 32A 6-aansluitingen 26 ACCES&GADGETS	LID16949