

Technische Fiche: LID17436--

Sutil Round2 LED 3W 240lm 3K/4K/5,7K IP20 230V 120° wit

Recessed downlight, Compleet met driver



Productinformatie

CCT Variable 3W slim downlight LED, IP20, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 300mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.


Technische gegevens

Hoogte (mm)	22,00
Netto diameter (mm)	85,00
Nettogewicht (kg)	0,14
Type verlichting	Inbouw plafondverlichting
Afwerking	Wit
Uitvoering	Acryl Aluminium gegoten
Afdekkingen	Acryl
Stralingshoek (°)	120
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Ingangsspanning AC (V)	220-240
Bedrijfsstroom mA (mA)	300

Technische gegevens - vervolg

Primaire stroom (A)	0,30
Lampvoet	LED
Lichtrendement (lm/W)	80
Vermogen (W)	3
Lichtkleur	Koudwit Warmwit Neutraalwit
Kleurtemperatuur (K)	4000 3000 5700
Kleurweergave-index (Ra)	≥80
Lichtstroom (lm)	240
Levensduur	36.000h / L70 / B50
Regelen lichtintensiteit	Neen
Beschermingsklasse	II
Beschermingsgraad	IP20
Inbouw diepte (mm)	50
Lichtmiddel inbegrepen	Inbegrepen
Diameter (mm)	85
ØxH (mm)	85x22
Boring voor inbouw (mm)	Ø 70
Uitsnijding (mm)	Ø 70

Maattekening: Sutil Round2 LED 3W 240lm 3K/4K/5,7K IP20 230V 120° wit



Omschrijving	Referentie
Sutil Round2 LED 3W 240lm 3K/4K/5,7K IP20 230V 120° wit	LID17436
Recessed downlight, Compleet met driver	