

Technische Fiche: LID17788--

Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V wit

Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable; CCTV PV 230V DARK LIGHT; 11 OFFICE & KITCHEN



Productinformatie

CCT and Power variable 40W UGR17 Linear system with 48 LED spots and uplight for suspended installation, ideal for offices. Complete with 2 x power variable drivers. Complies with standard EN60598-1 and any other specific standards.

Technische gegevens

Netto lengte (mm)	1.300,00
Breedte (mm)	35,00
Hoogte (mm)	70,00
Afwerking	Wit
Uitvoering	Aluminium
Stralingshoek (°)	34/120
Verblindingsfactor (UGR)	<17
Voedingen	LED Driver
Nominale werkspanning AC (V)	220-240
Ingangsspanning AC (V)	220-240
Lampvoet	LED
Lichtrendement (lm/W)	95

Technische gegevens - vervolg

Vermogen (W)	40 30 20
Lichtkleur	Koudwit Warmwit Neutraalwit
Kleurtemperatuur (K)	5000 4000 3000
Kleurweergave-index (Ra)	≥90
Lichtstroom (lm)	max. 1800/3800
Regelen lichtintensiteit	Nee
Beschermingsklasse	I
Beschermingsgraad	IP20
Diameter (mm)	68
LxBxH (mm)	1300x35x70

Maattekening: Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V wit



Omschrijving	Referentie
Linear BU LED 20-40W 3K/4K/5K CRI90 IP20 UGR17 230V wit	LID17788
Direct (20/30/40W) 34° / indirect (16/20/25W) 120°, 3m cable; CCTV PV 230V DARK LIGHT; 11 OFFICE & KITCHEN	