

Technische Fiche: LIMQ1L605A

M48 Area QU-D 2MOD 96LED 4000K IP66 227W 21545lm RAL9006

Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)



Technische gegevens

Type armatuur	Hal reflector armatuur
Montage	Pendelmontage Plafondopbouw
Kleur	RAL 9006
Materiaal	Aluminium
Voedingen	LED Driver
Werkspanning AC (V)	230
Lichtmiddel	LED
Lamphouder	LED printplaat
Vermogen (W)	227
Lichtkleur	Neutraalwit
Kleurtemperatuur (K)	4000
Kleurweergave-index	≥70
Lichtstroom (lm)	21545

Technische gegevens - vervolg

Aantal lampen	2
Beschermingsklasse	II
Beschermingsgraad	IP66
Inclusief lamp	ja
LxBxH mm	495x340x65

Artikelen

Omschrijving	Referentie
M48 Area QU-D 2MOD 96LED 4000K IP66 227W 21545lm RAL9006 Version with 2 Modules 96LEDs - SK.II - Power of luminaire 227W with Lumen output 21.545lm @700mA, Power of luminaire 166W with Lumen output 17.225lm @525mA, Power of luminaire 109W with Lumen output 12.425lm @350mA - "Economy" Version (ON-OFF)	LIMQ1L605A
Optionele toebehoren	
Plafondbeugel M48 Area RAL9006	LI06MQ900A
Staalkabelset l=1,5m M48 Area als pendelarmatuur	LI06MQ901J