


Technische Fiche: LITP0099--

LEILA II LED 12W/ 17W/ 23W 3000K/ 4000K/ 6000K 230VAC IP65 wit

Wall and ceiling luminaire for outdoor use; adjustable wattage and color temperature; 3000/4000/6000K; 12W = 1304 lm / 17W = 1847 lm / 23W = 2500 lm at 4000K; 108 lm/W at 4000K, Ø 320 mm




Lichtverdelingscurve



Technische gegevens

Hoogte (mm)	65,00
Netto diameter (mm)	320,00
Nettogewicht (kg)	0,80
Omgevingstemperatuur min. (°C)	-20
Omgevingstemperatuur max. (°C)	40
Type verlichting	Aanbouw wandverlichting Plafondverlichting
Bevestiging	Aanbouwmontage
Temperatuursbereik - Werking (°C)	-20°C tot +40
Afwerking	Wit
Stralingshoek (°)	120
Ingangsspanning AC (V)	220-240
Ingangsspanning DC (V)	300-330
Vermogen (W)	12 23 17
Lichtkleur	Warmwit Neutraalwit
Kleurtemperatuur (K)	4000 3500 3000
Kleurweergave-index (Ra)	80
MacAdam Kleurkwaliteit (sdcm)	5
Lichtstroom (lm)	2500
Levensduur	50000
Regelen lichtintensiteit	Nee
Beschermingsklasse	II
Beschermingsgraad	IP65
Slagvastheid	IK10
Diameter (mm)	320
ØxH (mm)	320x65

**Maattekening: LEILA II LED 12W/17W/23W 3000K/4000K/6000K 230VAC
IP65 wit**

Omschrijving	Referentie
LEILA II LED 12W/17W/23W 3000K/4000K/6000K 230VAC IP65 wit	
Wall and ceiling luminaire for outdoor use; adjustable wattage and color temperature; 3000/4000/6000K; 12W = 1304 lm / 17W = 1847 lm / 23W = 2500 lm at 4000K; 108 lm/W at 4000K, Ø 320 mm	LITP0099