

Technische Fiche: NCS4FWW14-

Security luminaire SECURO 24 CON S4 3W LED 24V DC

White, IP65, -25° up to +50°C, LED 3W, wall surface mounting, 318lm




Technische gegevens

Breedte (mm)	192,00
Hoogte (mm)	220,00
Diepte (mm)	65,00
Nettogewicht (kg)	1,12
Type verlichting	Noodverlichting
Type batterijvoeding	Centrale batterij
Type toestel	SECURO 24 CON
Productgroep	Verlichting metaal
Design	S4
Afwerking	Wit
Lichtmiddel	HP-LED (3W)
Lumen	314
Nominale stroom (mA) (mA)	180
Nominale spanning (V)	24VDC

Technische gegevens - vervolg

Beschermingsgraad	IP65
Bevestiging	Plafondmontage Plafondinbouw mogelijk
Omgevingstemperatuur min. (°C)	-25
Omgevingstemperatuur max. (°C)	50
AA Klasse E 8101	AA4
Leverancier	Schrack

Maattekening: Security luminaire SECURO 24 CON S4 3W LED 24V DC



Artikelen

Omschrijving	Referentie
Security luminaire SECURO 24 CON S4 3W LED 24V DC White, IP65, -25° up to +50°C, LED 3W, wall surface mounting, 318lm	NCS4FWW14
Optionele toebehoren	
Low Power Supply 24V DC SECURO 24 CON cab. M 6/20 w. batt. 6 circuits, max. 120 luminaires (20 luminaires per circuit), max. current per circuit: 3A, max. total load current in emergency mode: 1h: 18A, 3h: 8A, total max. 10A for maintained luminaires, with circuit monitoring, cabinet M (for 2 x 45Ah): H534 x W475 x D186mm, incl. 2 pcs 45Ah OGiV batteries (NLBA045)	NCCB2461-S
Low Power Supply 24V DC SECURO 24 CON cab. L 6/20 w. batt. 6 circuits, max. 120 luminaires (20 luminaires per circuit), max. current per circuit: 3A, max. total load current in emergency mode: 1h: 18A, 3h: 18A, total max. 10A for maintained luminaires, with circuit monitoring, cabinet L (for 4 x 45Ah): H754 x W475 x D186mm, incl. 4 pcs 45Ah OGiV batteries (NLBA045)	NCCB2463-S