

Notleuchteneinsatz NLKCW Autotest 3h

Complete replacement insert for fast upgrade 8W LL to LED, Autotest version with high-quality LiFePO4 battery, adjustable to 1h/3h/8h



Technische gegevens

Netto lengte (mm)	324,00
Breedte (mm)	140,00
Diepte (mm)	50,00
Nettogewicht (kg)	0,60
Type batterijvoeding	Autonome batterij
Type toestel	Noodverlichtng met autotest
Productgroep	Toebehoren
Design	KC
Lichtmiddel	LED (3W)
Lumen	300
Nominale spanning (V)	230VAC 50Hz ±20%
Continu vermogen (W)	3,30
Standby vermogen (W)	0,40
Maximaal vermogen (W)	4,20
Type batterij (V/Ah)	LiFePO4 2x 3,2V/ 1,6Ah
Omgevingstemperatuur min. (°C)	5
Omgevingstemperatuur max. (°C)	50

Technische gegevens - vervolg

AA Klasse E 8101

AA4

Leverancier

Schrack

Artikelen

Omschrijving	Referentie
Notleuchteneinsatz NLKCW Autotest 3h	
Complete replacement insert for fast upgrade 8W LL to LED, Autotest version with high-quality LiFePO4 battery, adjustable to 1h/3h/8h	NLKCWZ403S
Optionele toebehoren	
Set 2 accus LiFePO4 3,2V 1,6Ah f. luminaires. w. LEO or LPK	NLAKKU3216
LiFePO4 - Lithium-iron phosphate battery , UN3480 - UN 3480 : Lithium-Ion batteries	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV