

KWI Noodverlichting autotest LED 3h 230VAC plafond TT

With 2x 3,2/3,3Ah LiFePO₄ batteries suitable for low temperatures, -15°C up to 40°C, 1h/3h/8h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one side, viewing distance: 16m, IP65, IK06, protection class II, 1h: 300lm; 3h: 300lm; 8h: 120lm




Technische gegevens

Netto lengte (mm)	390,00
Breedte (mm)	93,00
Hoogte (mm)	139,00
Nettogewicht (kg)	1,30
Type verlichting	Noodverlichting
Type batterijvoeding	Autonome batterij
Type toestel	Autotest lage temperatuur
Productgroep	Kunststof verlichting
Design	KWI
Halogeenvrij	Behuizing van halogeenvrij kunststof
Afwerking	RAL 9003

Technische gegevens - vervolg

Pictogrammen	Set pictogrammen (pijl links, rechts, onder, boven) conform ISO 7010
Detectie afstand (m)	16
Lichtmiddel	LED (3W)
Lumen	1h: 300;3h: 300;8h: 120
Nominale spanning (V)	230VAC 50Hz $\pm 20\%$
Continu vermogen (W)	5,70
Standby vermogen (W)	2
Maximaal vermogen (W)	6,90
Type batterij (V/Ah)	LiFePO4 2x 3,2V/ 3,3Ah-TT
Beschermingsgraad	IP65
Slagvastheid	IK06
Bevestiging	Plafondmontage
Omgevingstemperatuur min. ($^{\circ}\text{C}$)	-15
Omgevingstemperatuur max. ($^{\circ}\text{C}$)	40
AA Klasse E 8101	AA4
Leverancier	Schrack

Dimensions (mm)



**Spacing table - Min. illuminance on the center line +/- 0.5 m: 1 lx -
Maintenance factor 0.80 - Autonomy time 1h/3h**

					
2,00	3,51	9,16	8,09	7,02	2,74
2,50	3,64	9,71	8,62	7,52	2,84
3,00	3,67	10,1	8,98	7,85	2,86
3,50	3,62	10,34	9,2	8,05	2,79
4,00	3,46	10,44	9,29	8,11	2,61
5,00	2,73	10,27	9,08	7,86	1,85

**Spacing table - Min. illuminance on the center line +/- 0.5 m: 1 lx -
Maintenance factor 0.80 - Autonomy time 8h**

					
2,00	1,88	5,55	5	4,37	1,48
2,50	1,6	5,55	4,99	4,34	1,2

Artikelen

Omschrijving	Referentie
KWI Noodverlichting autotest LED 3h 230VAC plafond TT	
With 2x 3,2/3,3Ah LiFePO4 batteries suitable for low temperatures, -15°C up to 40°C, 1h/3h/8h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one side, viewing distance: 16m, IP65, IK06, protection class II, 1h: 300lm; 3h: 300lm; 8h: 120lm	NLKWIDT03S
Optionele toebehoren	
KW Korf balbescherming	NLBKW
KWI Pictogrammen (pijlen boven, onder, links, rechts)	NLKWIPKTO
Set pictogrammen volgens ISO7010	
Pendelpaar 500mm bedraad wit	NL2PW
Wandbeugel voor KB/ KX/ KW/ KCD/ KE/ GX/ RX wit	NLAWX001
Batterij LiFePO4 3.2V 3.3Ah lage temperatuur	
LiFePO4 - Lithium-iron-phosphate battery suitable for low temperatures, UN3480 - LITHIUM-ION BATTERIES, The permissible ambient luminaire temperatures are specified for the low temperature luminaires	NLAKKU323T
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV