

Technische Fiche: NLMI104A--

Low Power Supply MicroControl 4 circ. total max. 80 lumin.

4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 500 W
1h / 200 W 3 h / 90 W 8 h, optionally expandable to max. 6 circuits max. 120 luminaires, h
x w x d: 630 x 350 x 720 mm



Technische gegevens

Netto lengte (mm)	230,00
Breedte (mm)	350,00
Hoogte (mm)	630,00
Nettogewicht (kg)	55,01

Artikelen

Omschrijving	Referentie
Low Power Supply MicroControl 4 circ. total max. 80 lumin.	
4 electrical circuits, max. 80 luminaires (20 luminaires per circuit), max. power rating: 500 W 1h / 200 W 3 h / 90 W 8 h, optionally expandable to max. 6 circuits max. 120 luminaires, h x w x d: 630 x 350 x 720 mm	NLMI104A
Optionele toebehoren	
E30 Schrank für Gruppebatt. MI	
Outside dimensions: 918 x 711 x 345mm (HxWxD), colour RAL7035, protection class II, IP54, 70kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMIE30
Plexiglas cover with lock for LPS Microcontrol	NLPLXMIC
3-fasen Netzüberw. mit Bus	NLMCLM
PC230 3-Fases-Netbewaking	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Indicator panel with LCD clear text display and bus comm.	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S