

Technische Fiche: NLPXW433WL

PX Noodverlichting WirelessControl LED 3h 230VAC

Exit sign: wall surface mounting, safety light: ceiling surface mounting, viewing distance: 30m, radio switchable, with LiFePO4 battery, 520lm



Technische gegevens

Netto lengte (mm)	340,00
Breedte (mm)	60,00
Hoogte (mm)	170,00
Nettogewicht (kg)	0,90
Type verlichting	Gecombineerde veiligheid en noodverlichting Noodverlichting
Type batterijvoeding	Autonome batterij
Type toestel	WirelessControl Professional
Productgroep	Kunststof verlichting
Design	PX
Halogeenvrij	Behuizing van halogeenvrij kunststof
Afwerking	RAL 9003
Pictogrammen	Pictogrammen conform ISO 7010 zijn inbegrepen
Detectie afstand (m)	30
Autonomietijd (h)	3
Lichtmiddel	ERT-LED (4W)

Technische gegevens - vervolg

Lumen	520
Nominale spanning (V)	230VAC 50Hz $\pm 20\%$
Continu vermogen (W)	5,70
Standby vermogen (W)	0,80
Maximaal vermogen (W)	7,50
Type batterij (V/Ah)	LiFePO4 2x 3,2V/ 3,3Ah
Beschermingsgraad	IP65
Slagvastheid	IK05
Bevestiging	Universeel Wandbevestiging Plafondmontage Plafondinbouw mogelijk
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	40
AA Klasse E 8101	AA4
Leverancier	Schrack

**Spacing table with square lens (for optimized illumination of the pictogram)
(included in scope delivery) - Minimum illuminance on the centerline at +/- 0.5
m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h**

					
2,00	5,03	11,47	11,47	11,47	5,03
2,50	5,75	13,22	13,22	13,22	5,75
3,00	6,35	14,79	14,79	14,79	6,35
3,50	6,59	16,2	16,2	16,2	6,59
4,00	6,69	17,48	17,48	17,48	6,69
5,00	4,78	18,72	18,72	18,72	4,78
6,00	2,9	17,57	17,57	17,57	2,9

Spacing table with corridor lens (NLLSYSF4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h

					
2,00	5,41	12,15	10,43	8,84	3,68
2,50	6,51	14,33	12,02	9,84	4
3,00	7,51	16,36	13,52	10,71	4,2
3,50	8,44	18,55	14,73	11,34	4,34
4,00	9,3	20,61	16,07	11,78	4,43
5,00	10,86	24,4	18,29	12,37	4,4
6,00	8,41	27,81	20,14	12,65	4,29
7,00	6,41	26,48	18,47	12,49	4,18
8,00	4,79	26,58	16,62	12,3	3,87
9,00	2,76	23,86	14,84	12,13	3,03

Spacing table with round lens (NLLSYSR4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h

					
2,00	4,21	9,38	9,38	9,38	4,21
2,50	5,05	10,9	10,9	10,9	5,05
3,00	5,81	12,56	12,56	12,56	5,81
3,50	6,51	14,22	14,22	14,22	6,51
4,00	7,14	15,77	15,77	15,77	7,14
5,00	7,55	18,58	18,58	18,58	7,55
6,00	4,89	19,41	19,41	19,41	4,89
7,00	3	18,4	18,4	18,4	3

Spacing table with spot lens (NLLSYSS4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 1h/3h

					
2,00	1,91	4,79	4,79	4,79	1,91
2,50	2,39	5,99	5,99	5,99	2,39
3,00	2,87	7,19	7,19	7,19	2,87
3,50	3,33	8,39	8,39	8,39	3,33
4,00	3,57	8,74	8,74	8,74	3,57
5,00	4,04	9,53	9,53	9,53	4,04
6,00	4,51	10,45	10,45	10,45	4,51
7,00	4,88	11,4	11,4	11,4	4,88
8,00	5,26	12,39	12,39	12,39	5,26
9,00	5,56	13,23	13,23	13,23	5,56
10,00	5,78	13,93	13,93	13,93	5,78
12,00	6,02	15,36	15,36	15,36	6,02
14,00	5,98	16,35	16,35	16,35	5,98
16,00	5,67	16,93	16,93	16,93	5,67

Spacing table with high corridor lens (NLLSYSH4 must be ordered separately)
- Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 -
Autonomy time 1h/3h

					
2,00	2,2	5,89	7,64	9,38	4,09
2,50	2,75	7,36	9,55	11,73	5,12
3,00	3,28	8,73	11,31	13,87	6,05
3,50	3,34	9,06	12,13	15,12	6,7
4,00	3,35	9,27	12,88	16,55	7,29
5,00	3,27	9,5	14,34	19,2	8,23
6,00	2,74	9,51	15,51	21,52	8,89
7,00	2,57	9,35	16,35	23,36	9,38
8,00	2,65	8,59	16,65	24,76	9,72
9,00	2,66	7,66	16,65	25,97	9,9
10,00	2,62	7,25	16,9	26,85	9,98
12,00	2,62	7,55	16,92	28,07	8,99
14,00	2,39	7,41	15,75	28,23	8,54
16,00	1,98	7,5	15,31	26,42	7,13

Artikelen

Omschrijving	Referentie
PX Noodverlichting WirelessControl LED 3h 230VAC Exit sign: wall surface mounting, safety light: ceiling surface mounting, viewing distance: 30m, radio switchable, with LiFePO4 battery, 520lm	NLPXW433WL
Optionele toebehoren	
KC Regendak plexiglas	NLKCRD
Korf balbescherming KC/ KB/ KBG/ KX/ PF/ LX/ RX LxBxH 450x280x125mm	NLBALL2
Set 2 accus LiFePO4 3,2V 3,3Ah f. luminaires. w. LEO or LPK LiFePO4 - Lithium-iron phosphpate battery , UN3480 - UN 3480 : Lithium-Ion batteries	NLAKKU323L
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV