

Technische Fiche: SR3PDIEM02

PDU Essential Metered; 6xSchuko; 230V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 6xCEE7/3 35° Socket
- Supply cable: 2.0m | 1.5mm²
- with CEE7/7 angled plug
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technische gegevens

Netto lengte (mm)	437,40
Breedte (mm)	45,00

Technische gegevens - vervolg

Hoogte (mm)	60,00
Nettogewicht (kg)	0,90
EAN CODE	4057298233029
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	45
Nominale spanning	230V
Beschermingsgraad	IP20
Type product	Metered Essential
Aantal stopcontacten	6
Type connector	6 x Schuko
Nominale stroom (A)	16
Fasen per voeding	1
Type aansluiting	CEE 7/7 (Type E/F)
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Bevestiging	Bevestigingshoek (L-vormig)

Omschrijving	Referentie
PDU Essential Metered; 6xSchuko; 230V; 16A	SR3PDIEM02
Measurement per phase, incl. mounting bracket with screws	