

Technische Fiche: SR3PDIEM04

PDU Essential Metered; 4xC13; 2xC19; 230V; 16A

Messung pro Phase, inkl. Befestigungswinkel mit Schrauben



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 4xC13 0° IEC Socket 2xC19 90° IEC Socket
- Power Supply: with C20 Built-In Connector
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technische gegevens

Netto lengte (mm)	437,40
-------------------	--------

Technische gegevens - vervolg

Breedte (mm)	45,00
Hoogte (mm)	60,00
Nettogewicht (kg)	1,00
EAN CODE	4057298233050
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	45
Nominale spanning	230V
Beschermingsgraad	IP20
Type product	Metered Essential
Aantal stopcontacten	6
Type connector	4 x IEC320 C13 und 2 x IEC320 C19
Nominale stroom (A)	16
Fasen per voeding	1
Type aansluiting	C20
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Bevestiging	Bevestigingshoek (L-vormig)

Omschrijving	Referentie
PDU Essential Metered; 4xC13; 2xC19; 230V; 16A	SR3PDIEM04
Messung pro Phase, inkl. Befestigungswinkel mit Schrauben	