

Technische Fiche: SR3PDIEM05

PDU Essential Metered; 24xC13; 3xC19; 230V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 24xC13 0° IEC Socket 3xC19 90° IEC Socket
- Supply cable: 3.0m | 2,5mm²
- with CEE 16A plug, blue
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technische gegevens

Technische gegevens - vervolg

Netto lengte (mm)	1.000,00
Breedte (mm)	45,00
Hoogte (mm)	60,00
Nettogewicht (kg)	2,80
EAN CODE	4057298233067
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	45
Nominale spanning	230V
Beschermingsgraad	IP20
Type product	Metered Essential
Aantal stopcontacten	27
Type connector	24 x IEC320 C13 und 3 x IEC320 C19
Nominale stroom (A)	16
Fasen per voeding	1
Type aansluiting	CEE Stekker 16A blauw
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Bevestiging	Bevestigingshoek (L-vormig)

Omschrijving	Referentie
PDU Essential Metered; 24xC13; 3xC19; 230V; 16A	SR3PDIEM05
Measurement per phase, incl. mounting bracket with screws	