

Technische Fiche: SR3PDIEM08

# PDU Essential Metered; 24xC13; 4xC19; 230V; 32A

Measurement per phase, incl. mounting bracket with screws



## SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 32A/230V | 7,2kW Output: 24xC13 0° IEC Socket 4xC19 90° IEC Socket
- 2xMiniature Circuit Breaker C16A
- split into two blocks, each block
- fused with a MCB
- Supply cable: 3.0m | 4mm<sup>2</sup>
- with CEE 32A plug, blue
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

## Technische gegevens

|                                |                                                                                                                                  |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Netto lengte (mm)              | 1.170,60                                                                                                                         |
| Breedte (mm)                   | 45,00                                                                                                                            |
| Hoogte (mm)                    | 94,00                                                                                                                            |
| Nettogewicht (kg)              | 3,50                                                                                                                             |
| EAN CODE                       | 4057298233104                                                                                                                    |
| Omgevingstemperatuur min. (°C) | -5                                                                                                                               |
| Omgevingstemperatuur max. (°C) | 45                                                                                                                               |
| Nominale spanning              | 230V                                                                                                                             |
| Beschermingsgraad              | IP20                                                                                                                             |
| Type product                   | Metered Essential                                                                                                                |
| Aantal stopcontacten           | 28                                                                                                                               |
| Type connector                 | 24 x IEC320 C13 und 4 x IEC320 C19                                                                                               |
| Nominale stroom (A)            | 32                                                                                                                               |
| Fasen per voeding              | 1                                                                                                                                |
| Type aansluiting               | CEE Stekker 32A blauw                                                                                                            |
| Protocol                       | CLI<br>IPv6<br>IPv4<br>DNS<br>SMTPS<br>SSH<br>HTTP<br>NTP<br>DHCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog<br>SNMPv2/v3<br>Telnet |
| Bevestiging                    | Bevestigingshoek (L-vormig)                                                                                                      |

| Omschrijving                                              | Referentie |
|-----------------------------------------------------------|------------|
| PDU Essential Metered; 24xC13; 4xC19; 230V; 32A           | SR3PDIEM08 |
| Measurement per phase, incl. mounting bracket with screws |            |