

Technische Fiche: SR3PDIPM09

PDU PRO Metered, 36xC13, 6xC19, 400V, 32A

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 36x C13 IEC Socket + 6 x C19 IEC Socket
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 2075 mm

Technische gegevens

Netto lengte (mm)	2.075,00
Breedte (mm)	56,00
Hoogte (mm)	65,00
Nettogewicht (kg)	6,77
EAN CODE	4057298207938
Adviesprijs	3.562,00
Omgevingstemperatuur min. (°C)	0
Omgevingstemperatuur max. (°C)	50
Nominale spanning	400V
Beschermingsgraad	IP20
Type product	Metered
Aantal stopcontacten	42
Type connector	36 x IEC320 C13 und 6 x IEC320 C19
Nominale stroom (A)	32
Fasen per voeding	3
Type aansluiting	CEE Stekker 32A rood
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Bevestiging	Bevestigingshoek (L-vormig)

Omschrijving	Referentie
PDU PRO Metered, 36xC13, 6xC19, 400V, 32A Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!	SR3PDIPM09