

Technische Fiche: SR3PDIPP01

PDU PRO Metered+, 24xCombo Outlets (C13, C15, C19, C21), 230V, 16A

Metering per outlet, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 16 A / 230 V | 3.6 kW
- Input: 3.0 m | 2.5 mm²
- with CEE plug 16 A blue
- Output: 24x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </I

Technische gegevens

Netto lengte (mm)	1.191,00
Breedte (mm)	56,00
Hoogte (mm)	71,00
EAN CODE	4057298230257
Adviesprijs	3.843,00
Omgevingstemperatuur min. (°C)	0
Omgevingstemperatuur max. (°C)	50
Nominale spanning	230V
Beschermingsgraad	IP20
Type product	Metered+
Aantal stopcontacten	24
Type connector	24 x Combo Socket (C13/C15/C19/C21)
Nominale stroom (A)	16
Fasen per voeding	1
Type aansluiting	CEE Stekker 16A blauw
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Bevestiging	Bevestigingshoek (L-vormig)

Omschrijving	Referentie
PDU PRO Metered+, 24xCombo Outlets (C13, C15, C19, C21), 230V, 16A	SR3PDIPP01
Metering per outlet, incl. mounting bracket with screws	